

DS-3500

EXPAND YOUR NETWORK OF PRODUCTIVITY

The DS-3500 Professional Dictation System from Olympus is a robust, user-friendly tool for improving organizational efficiency.

Featuring intuitive push-button controls and multiple recording formats, the DS-3500 is the ideal solution for streamlined data entry or conference recording. The included Olympus Dictation Management System software integrates directly with existing workflows, third-party applications and voice-recognition software, allowing users to automatically route files for transcription or archiving, and manage preferences and security settings individually or system-wide.



Features

- ▶ Includes Olympus Dictation Management System software
- ▶ Easily integrated with existing software, applications and workflows
- ► Transfer files via USB, cradle or remotely with a FlashAirTM SD card
- ▶ Real-time 256-bit file encryption and device PIN locking
- ▶ Awarded the highest level Dragon score (6) from Nuance

Use case:

Capture all the details of every important meeting When equipped with one of Olympus' external microphone kits, the DS-3500 becomes the ideal solution for **capturing every detail of business meetings** or **conference calls** – and immediately routing the recording files for transcription or archiving.



DS-3500 Specifications

	Olympus DS-3500 Professional Dictation System
KEY FEATURES	Durk hattage
Main switch (REC/STOP/PLAY/RWD) Display	Push buttons Color TFT-display with white LCD backlight Resolution: 176 x 220 pixel Size: 34 x 42 mm / 1.3 x 1.7 inch
Battery	Rechargeable Li-ion-battery (710mAh) Up to 26 hours of recording time with one battery charge
Data security	DSS Pro real-time encryption (128- / 256-Bit)
Storage media	Secure Digital (SD, SDHC), 2GB-32GB
Internal storage media	2GB (micro SD), DSS Pro SP = approx. 306 hours recording time
RECORDING FORMATS	
DSS/DSS Pro	Quality play (16kHz / 28kbps) Standard play (12kHz / 13.7kbps)
PCM (mono/stereo); MP3	✓
PROFESSIONAL SPEECH PROCESSING	
Author IDs	10
Worktypes	20
Priority	High / Normal
Verbal comments, Text editor, Pending, File lock	✓
ADVANCED RECORDING FEATURES	
Voice activated recording (VCVA)	✓
Microphone sensitivity	Dictation / Conference
Insert, Overwrite, Append, Partially erase	Only with DSS Pro & DSS
Index	32 (DSS Pro), 16 (DSS, MP3, WAV)
Level meter, VCVA indicator	✓
Folders	Up to 7 (name changeable)
Hands-free dictation, stand-alone transcription	With optional Olympus Footswitch RS-31
Full-duplex recording	With headphones
PLAYBACK	
Speed	Slow / Normal / Fast
Volume level	Adjustable from 0 to 30
STATIONARY OPERATIONS	
Annii bi BC i b	,
Applicable as PC microphone	V
Controlling PC application ODMS	✓ ✓
	Various settings related to user authorization, e.g., prohibiting erasing of files; menu settings
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility	e.g., prohibiting erasing of files; menu settings
Controlling PC application ODMS ADMINISTRATIVE SETTINGS	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional)	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems Recommended operating condition	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3 114.5×50×17mm / 4.5×2×0.7inch; 107g (including battery) / 3.8 oz English, Spanish, French Microsoft Windows XP, Vista, 7, 8 (Pro and Enterprise); Mac OS X.5-9 0-42°C / 32-107.6°F
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems Recommended operating condition USB	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3 114.5×50×17mm / 4.5×2×0.7inch; 107g (including battery) / 3.8 oz English, Spanish, French Microsoft Windows XP, Vista, 7, 8 (Pro and Enterprise); Mac OS X.5-9 0-42°C / 32-107.6°F Mini USB 2.0 composite / storage class
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems Recommended operating condition USB Charging	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3 114.5×50×17mm / 4.5×2×0.7inch; 107g (including battery) / 3.8 oz English, Spanish, French Microsoft Windows XP, Vista, 7, 8 (Pro and Enterprise); Mac OS X.5-9 0-42°C / 32-107.6°F Mini USB 2.0 composite / storage class Via AC adapter or USB
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems Recommended operating condition USB Charging Speaker (integrated)	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3 114.5×50×17mm / 4.5×2×0.7inch; 107g (including battery) / 3.8 oz English, Spanish, French Microsoft Windows XP, Vista, 7, 8 (Pro and Enterprise); Mac OS X.5-9 0-42°C / 32-107.6°F Mini USB 2.0 composite / storage class Via AC adapter or USB Ø 23mm / 0.9inch, 300mW
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems Recommended operating condition USB Charging Speaker (integrated) Headphone jack	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3 114.5×50×17mm / 4.5×2×0.7inch; 107g (including battery) / 3.8 oz English, Spanish, French Microsoft Windows XP, Vista, 7, 8 (Pro and Enterprise); Mac OS X.5-9 0-42°C / 32-107.6°F Mini USB 2.0 composite / storage class Via AC adapter or USB Ø 23mm / 0.9inch, 300mW Stereo, 3.5mm / 0.1inch, 2k
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems Recommended operating condition USB Charging Speaker (integrated) Headphone jack Microphone jack	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3 114.5×50×17mm / 4.5×2×0.7inch; 107g (including battery) / 3.8 oz English, Spanish, French Microsoft Windows XP, Vista, 7, 8 (Pro and Enterprise); Mac OS X.5-9 0-42°C / 32-107.6°F Mini USB 2.0 composite / storage class Via AC adapter or USB Ø 23mm / 0.9inch, 300mW Stereo, 3.5mm / 0.1inch, 2k Stereo, 3.5mm / 0.1inch, 8k
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems Recommended operating condition USB Charging Speaker (integrated) Headphone jack Microphone jack Toshiba FlashAir™ card compatibility	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3 114.5×50×17mm / 4.5×2×0.7inch; 107g (including battery) / 3.8 oz English, Spanish, French Microsoft Windows XP, Vista, 7, 8 (Pro and Enterprise); Mac OS X.5-9 0-42°C / 32-107.6°F Mini USB 2.0 composite / storage class Via AC adapter or USB Ø 23mm / 0.9inch, 300mW Stereo, 3.5mm / 0.1inch, 2k Stereo, 3.5mm / 0.1inch, 8k
Controlling PC application ODMS ADMINISTRATIVE SETTINGS Accessibility Splash message Alarms Customizable display content Programmable buttons ADMINISTRATIVE SETTINGS Single user and workgroup installation Server installations including license manager and manager tools (optional) Citrix / WTS / Thin client support TECHNICAL DATA Dimensions (H×W×D); weight Languages Operating systems Recommended operating condition USB Charging Speaker (integrated) Headphone jack Microphone jack Toshiba FlashAir™ card compatibility	e.g., prohibiting erasing of files; menu settings Option to set personalized welcome message during start-up Option to set alarms for particular occasions; beeping noise Option to customize information shown on display 3 114.5×50×17mm / 4.5×2×0.7inch; 107g (including battery) / 3.8 oz English, Spanish, French Microsoft Windows XP, Vista, 7, 8 (Pro and Enterprise); Mac OS X.5-9 0-42°C / 32-107.6°F Mini USB 2.0 composite / storage class Via AC adapter or USB Ø 23mm / 0.9inch, 300mW Stereo, 3.5mm / 0.1inch, 2k Stereo, 3.5mm / 0.1inch, 8k microSD card, Li-ion battery, USB cable, Olympus Dictation Management Systems



DS-3500 PROFESSIONAL

DICTATION SYSTEM

Secure. Reliable. Integrated.

The DS-3500 Professional Dictation System from Olympus is designed to dramatically improve efficiency for any user or organization, and within any IT environment.



Cradle is an optional accessory





